

PLANITHERM® ONE T



Description

PLANITHERM ONE T is manufactured on a magnetron coater. A unique combination of metal oxide layers are applied to high quality PLANICLEAR clear float glass using a magnetically enhanced cathodic sputtering process under vacuum conditions.

Range

Monolithic Glass:

Standard thickness: 4mm and 6mm. Other thicknesses are available upon request including 8mm and 10mm.
Substrate: PLANICLEAR clear float.

Toughened Glass:

PLANITHERM ONE T is a “single-stock” coating and therefore can be used in either annealed or toughened form. It can be toughened to meet the safety requirements of BS EN 12150.

Laminated Glass:

STADIP, STADIP PROTECT and STADIP SILENCE laminated glass - please contact us for lead times and availability.

Applications

PLANITHERM ONE T is a low-E glass offering the lowest centre pane U-value in the PLANITHERM

family providing excellent thermal insulation for the most demanding of glass specifications:

Residential New Build Solutions:

- Windows and skylights
- Patio doors, French doors and other external doors

Commercial New Build and Renovation Solutions:

- Façades and windows
- Structural glazing
- Overhead glazing

Find out more at www.planitherm.com

Find out More



Thermal Insulation Glazing



SGG PLANITHERM® FAMILY

[Find a distributor](#)